






ZHENGZHOU FIVE STAR LIGHTING CO., LTD.

www.fsdlighting.com

http://fivestarlight.en.alibaba.com

Tel: +86-371-63223999 Mob: +86-13598018017 E-mail: admin@fsdlighting.com NO.66 JINGSAN ROAD, JINSHUI DISTRICT, ZHENGZHOU, CHINA





Our vision:

Become one of the mainstream lighting suppliers in the world

Our mission:

Bringing Color to the World Lighting

Wherever

you go...

Street and road luminaires of the chinese manufacturer FSD Lighting represent modern solutions, energy efficiency, durability and safety. They provide both effective and eye catching lighting.

Our luminaires are characterised by:

- Excellent quality at a competitive price
- Design developed by our own R&D department
- Efficiency up to 170 lm/W
- Power range from 25w to 1800 W
- Luminous flux range from 1,500 to 25,200 lm
- Very high IP66 ingress protection
- Wide range of light distribution

COMPANY PROFILE

Zhengzhou five star Lighting Co., Ltd. is a professional and comprehensive LED lighting solution provider in China, engaged in the design, R&D, manufacturing, sales and service of outdoor LED lighting products, covering industrial lighting, commercial lighting, intelligent lighting and other fields.

The department of international commerce is located in Zhengzhou, has 500 square meters and 30 employees. the manufacturing department was established in 2012. The factory is located in Shenzhen and Zhongshan and other places, with about 5500 square meters and 150 employees.

Our products have passed CCC, FCC, UL, SAA, CE, RoHS, and many other international quality system certifications. At present, our products have been exported to more than 70 countries in North America, South America, Europe, the Middle East, Africa, Southeast Asia, etc., and have been unanimously recognized by customers.

In addition, we are also committed to integrating China's top qualified manufacturers to provide various customized lighting products to meet the different needs of customers. We adhere to the principle of mutual benefit and help our customers gain market leadership with professional services, high-quality products and competitive prices.

Whether you need any of our products or are looking for help with engineered lighting, please feel free to contact us. Looking forward to cooperating with you and presenting satisfactory products for you!





" LED
Street Light"







High efficiency 130lm/w, 150lm/w, 170lm/w available

Material: ADC12/Alu

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 50000h Warranty: 5years





| Model type | Beam angle | Colour temperature | Efficiency |
|------------|------------|-----------------------|------------|
| FSD-G7 | 60/90/120 | 2800K-6000K | 120-170lm/ |







0/1-10v dimming, microwave sensor, daylight sensor available

Material: ADC12/Alu

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 50000h Warranty: 5years







| 多角點 | IP65 [1965] | C€ F© Ro | HS |
|------------|-------------|-------------|-----------------------|
| Model type | Beam angle | Efficiency | Colour temperature |
| FSD-G7 | 60//90/120° | 120-170lm/w | 2800-6000k |







FSD-G6

Best waterproof Ip66 automatic

Material: ADC12/Alu

Led light source: Philips 3030 Led driver: Meanwell/sosen

Life span: 20000h Warranty: 5years





| Model type | Beam angle | Efficiency | Colour temperature |
|------------|-------------|-------------|-----------------------|
| FSD-G6 | 60//90/120° | 120-170lm/w | 2800-6000k |



FSD-G6

Hihighway lighting system dimmable

Material: ADC12/Alu

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 20000h Warranty: 5years





| Model type | Beam angle | Efficiency | Colour temperature |
|------------|-------------|-------------|-----------------------|
| FSD-G6 | 60//90/120° | 120-170lm/w | 2800-6000k |



FSD-G6

Patent Professional Black With Light Sensor

Material: ADC12/Alu

Led light source: Philips 3030 Led driver: Meanwell/sosen

Life span: 20000h Warranty: 5 years





| Model type | Beam angle | Efficiency | Colour temperature |
|------------|-------------|-------------|-----------------------|
| FSD-G6 | 60//90/120° | 120-170lm/w | 2800-6000k |



FSD-G6

Smart Led Street Light Ip66

Material: ADC12/Alu

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 20000h Warranty: 5years





| Model type | Beam angle | Efficiency | Colour temperature |
|------------|-------------|-------------|-----------------------|
| FSD-G6 | 60//90/120° | 120-170lm/w | 2800-6000k |



" Solar Light "



FSD-YXR

Remote control distance up to 15 meters

Working Time: 12-15 hours (5-7 rainy days) Battery: Built-in large capacity LifePO4 battery

Material: Imported high-efficiency monocrystalline silicon

Control Mode: Time control + Microwave induction or Infrared induction

Warranty: 3 years









| Model type | LED Type | Colour temperature | Efficiency |
|------------|----------|-----------------------|-------------|
| FSD-YXR | 5050 | 2700K-6500K | 120-180lm/w |





Intelligent charge and discharge controller

CRI (Ra>): 70

Lifespan: 50000hours LED Light Source: epistar Mounting height(m): 4-5

IP Rating: IP65





| Model type | Input Voltage | Working Time | Lamp Body Material |
|------------|---------------|--------------|-----------------------|
| FSD-HT | DC12V | 20000hours | Aluminum A |





FSD-HT2

Remote control all in one solar automatic light

CRI (Ra>): 70

Lifespan: 50000 hours

IP Rating: IP65

Remote Control:2-6 meters

Lithium Battery: 3.2V/5AH,3.2V/10AH,3.2V/15AH



| 多相對 | IP65 0145° | CE F© Rol | HS |
|------------|---------------|--------------|-----------------------|
| Model type | Input Voltage | Working Time | Lamp Body Material |
| FSD-HT2 | DC12V | 10-12hours | ABS |
| | | | |



FIWE STAR

FSD-SD

Wind and photovoltaic hybrid power

Material: Alu + glass

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 60000h Warranty: 5years





| Model type | Beam angle | Efficiency | Colour temperatu |
|------------|------------|-------------|---------------------|
| FSD-SD | 60/90/120° | 120-170lm/w | 2800K-600 |





FSD-SD

Hot dip galvanizing + electrostatic coating pole

Material: Alu + glass

Led light source: Philips 3030

Led driver: Meanwell/sosen

Life span: 60000h Warranty: 5years





| Model type | Beam angle | Efficiency | Colour temperature |
|------------|------------|-------------|-----------------------|
| FSD-SD | 60/90/120° | 120-170lm/w | 2800K-6000K |



FIWE STAR

FSD-HT3

Intelligent remote control, light operated

Solar Panel: 10V/50w SMD Chip: San'an 5730

Battery: 6.4v/25AH/10 batteries

Charge and discharge times: ≥1200times

Service life: 2 years for battery,3-5 years for solar panel





| Model type | Packaging | Charging | IP Rank |
|------------|------------|----------|-----------|
| FSD-HT3 | 19.5kg/CTN | 4-6hours | IP65-IP67 |







" LED Flood Light "





0/1-10V dimming, time control

IP Rank: IP66

Warranty: 5years

Lens: Glare free lens

Color: Matte black, Silver grey, other colors customizable

LED Driver: Able to match Meanwell and other mainstream drivers in the market





| Model type | LED Type | Efficiency | Colour temperature |
|------------|-----------------------|-------------|-----------------------|
| FSD-GLT | Lumileds 3030/5050 | 120-150lm/w | 2800-6500 |









Good heat dissipation, long lifespan

IP Rank: IP66

Warranty: 5years

Power: 10-350W (Customized)

Beam angle: 30°/60°/90°/120°/T2M/T3M Cover: Good heat dissipation, long lifespan,

excellent corrosion-proof





| Model type | LED Type | Efficiency | Colour temperature |
|------------|------------------|------------|-----------------------|
| FSD-GLT | Lumileds 3030 | 120lm/w | 3000-6500k |





FSD-GLT

Patent private mould, integrated die-casting AL

CRI: Ra>80

IP Rank: IP66

Warranty: 5years

Lens angle: 7°/15°/30°/60°/90°/120°/T2M/T3M/T4M Cover: Good heat dissipation, long lifespan, excellent

corrosion-proof





| Model type | LED Type | Efficiency | Colour temperature |
|------------|-----------|-------------|-----------------------|
| FSD-GLT | 3030/5050 | 100-150lm/w | 3000-6000 |





FSD-GLT

0/1-10V dimming, microwave sensor, daylight sensor available

PF:>0.9

THD: ≤15%

Warranty: 5years

Luminous Flux: 6750LM±10%, 13500LM±10%

Lens Angle: 15°/30°/60°/90°/120°/T2M/T3M/30*90°/50*120°for option





| Model type | LED Type | Efficiency | Colour temperature |
|------------|----------|------------|-----------------------|
| FSD-GLT | 2835 | 140lm/w | 3000-6000k |





" High bay
Light"







Glare-free design, UGR<25

Material: Aluminum

Led Light Source: PCT 3030 Led Driver: Meanwell/sosen

Life Span: 50000h Warranty: 5years





| Model type | Beam angle | Colour temperature | Efficiency |
|------------|------------|-----------------------|------------|
| FSD-S1 | 60/90 | 2800K-6000K | 120-150lm/ |





FSD-GLT

1-10V dimmable, microwave sensor available

IP Rank: IP65

Power(w):100-240

Voltage: AC100V-240V 50/60HZ

Warranty: 5years

Luminous Flux: 12000LM ±5%, 18000LM ±5%,





| Model type | LED Type | Efficiency | Colour temperature |
|------------|----------|-------------|-----------------------|
| FSD-GLT | Lumileds | 120-130lm/w | 2800-6500k |







ZigBee pwm 0/1~10v micro-wave available

Surge Protection: 4KV

Led Light Source: San'an 2835

Led Driver: Able to match Meanwell and other mainstream drivers in the market

Life Span: 50000h Warranty: 5years





| Model type | Beam angle | Colour temperature | Thermal Conductivit |
|------------|--------------|-----------------------|------------------------|
| YXR-UFOB | 60°/90°/120° | 2800K-6500K | 96 W/m⋅K |







ZigBee pwm 0/1~10v micro-wave available

Surge Protection: 6KV

Led light source: LUMILEDS 3030

Led driver: Able to match Meanwell and other mainstream drivers in the market

Life span: 50000h Warranty: 5years



WAND OF THE



| | IP65 (1945) | C€ F© Ro | НЅ |
|------------|--------------|-----------------------|--------------|
| Model type | Beam angle | Colour temperature | Input voltaç |
| YXR-UFOF | 60°/90°/130° | 3000K-6500K | AC100-305 |




FSD-QC

Meanwell LED driver AC 100-305v

Material: Aluminum+PC Led Type: LUMILEDS 5050 Led driver: Meanwell

Life span: 50000h Warranty: 5years





| Model type | Beam angle | Colour temperature | Efficiency |
|------------|--------------|-----------------------|-------------|
| FSD-QC | 10/25/45/60° | 3500K-6500K | 120-170lm/w |







IP54 with PC cover, free of dust and small splash water

Surge Protection: 6KV

Led light source: San'an/Lumileds 3030

Led driver: Able to match Meanwell and other mainstream drivers in the market

Life span: 50000h Warranty: 5years





| Model type | Beam angle | Colour temperature | Efficiency |
|------------|------------------|-----------------------|------------|
| YXR-A | 45°/60°/90°/120° | 2800K-6500K | 120lm/w |



" Solar Garden Light"





FSD-HY

Automatically and brightness sensing

Material: ABS + PC

Solar Panel: Polycrystalline sillicon

Light Source: SMD2835 LED

Working Temperature(°C): -20 - 60

Working Time: 6-12hours





| Model type | Life span | Colour temperature | Warranty |
|------------|-----------|-----------------------|----------|
| FSD-HY | 50000h | 2500k-7000k | 1years |





FSD-CP

Like flower basket in the garden

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 50LED

Working Temperature(°C): -20 - 60

Working Time: 6-12H





| Model type | Product size | G.W | Function |
|------------|---------------|-------|------------------------------|
| FSD-CP | 580*540*375mm | 0.5kg | Intelligent light control |



FSD-TY

Bright and warm the pathway garden night

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 16LED

Working Temperature(°C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|--------|------------------------------|
| FSD-TY | 130*650mm | 0.47kg | Intelligent light control |





New style and new design for night lighting

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 16LED

Working Temperature(°C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|-------|-------------|
| FSD-QY | 135*780mm | 1.1kg | Intelligent |





FSD-SD

Mutil-function and single-end

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 4LED

Working Temperature(°C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|--------|--------------------------|
| FSD-SD | 270*80*260mm | 0.34kg | Intelliger light cont |





FSD-SD

Mutil-function and double-end

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 36LED

Working Temperature(°C): -20 - 60







FSD-CP

Halo new lawn lights

Material: ABS + PC

Solar Panel: A-Si(Amorphous Silicon)

Light Source: LED

Working Temperature(°C): -20 - 60

Working Time: 6-12H





| Model type | G.W | Carton | Light color |
|------------|-------|--------|-----------------|
| FSD-CP | 2.2kg | 96pcs | White/warm ligh |



FSD-CP

Retro style and black design

Material: ABS + PC

Solar Panel: A-Si(Amorphous Silicon)

Light Source: LED

Working Temperature(°C): -20 - 60





| Model type | G.W | Carton | Switch |
|------------|-------|--------|-------------------|
| FSD-CP | 1.1kg | 6pcs | Green plug switch |



FSD-BD

Long bright and large angle of light

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 48LED

Working Temperature(°C): -20 - 60

Working Time: 6-12H





| Model type | G.W | Product size | Function |
|------------|-------|---------------|-----------------------------|
| FSD-BD | 0.8kg | 210*190*175mm | Intelligent light contro |



FSD-SD

High power lamp bead

Material: ABS + Alu

Solar Panel: A-Si(Amorphous Silicon)

Light Source: LED

Working Temperature(°C): -20 - 60





| Model type | G.W | Product size | Function |
|------------|-------|--------------|------------------------------|
| FSD-SD | 0.9kg | 73*315mm | Intelligent light control |



" Solar Wall Light"







Multifunctional and fashionable for your life

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 36LED

Working Temperature(°C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|--------|------------------------------|
| FSD-BD | 155*110*60mm | 0.38kg | Intelligent light control |







FSD-BD

Square window sconces in the wall

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 2LED

Working Temperature(°C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|--------|-----------------------------|
| FSD-BD | 89*52*114mm | 0.38kg | Intelligent light contro |







FSD-BD

Facing the smile in front of human

Material: ABS + PC

Solar Panel: Monocrystalline silicon plate

Light Source: 3LED

Working Temperature($^{\circ}$ C): -20 - 60





| Model type | Product size | G.W | Function |
|------------|--------------|--------|----------------------------|
| FSD-BD | 105*40*100mm | 0.08kg | Intelligent light contr |



FSD-SD

Shark head appearance modeling

Material: ABS + Alu

Solar Panel: A-Si(Amorphous Silicon)

Light Source: LED

Working Temperature(°C): -20 - 60





| Model type | G.W | Product size | Function |
|------------|-------|--------------|------------------------------|
| FSD-SD | 0.4kg | 206*113*92mm | Intelligent light control |



" Housing
Assembly Kit "








Thickened heat dissipation design

Material: ADC12/Alu

Led light source: Philips 3030

PCB model: 8C18B

Weight of sink heat(kg): 2.1







FSD-LD-K


Thickened heat dissipation design

Material: ADC12/Alu

Led light source: Philips 3030

PCB model: 8C18B

Weight of sink heat(kg): 1.6







FSD-TC-K

Thickened heat dissipation design

Material: ADC12/Alu

Led light source: Philips 3030

PCB model: 6C/8CC

Beam angle: 15/30/60/90





| Model type | Powe | Heat sink weight | Heat sink size |
|------------|------------------|---------------------|-------------------|
| FSD-TC-K | 100/150/200/300w | 3.35kg | 228*95*1.6m |





FIWE STAR

FSD-KD-K

Thickened heat dissipation design

Material: ADC12/Alu

Led light source: Philips 3030

PCB model: 7C20B Beam angle: 60/90/120





| Model type | Power | Heat sink weight | Heat sink size |
|------------|------------------|---------------------|-------------------|
| FSD-KD-K | 100/150/200/300w | 0.61kg | 240*49mn |






FSD-QC-K

Thickened heat dissipation design

Material: ADC12/Alu

Led light source: Philips 3030

PCB model: 7C45B*1 Beam angle: 15/30/60/90





| Model type | Power | Heat sink weight | Heat sink size |
|------------|--------------|---------------------|-------------------|
| FSD-QC-K | 200/600/800w | 1.6kg | Ф400*85mn |





FSD-JR

Super heat dissipation performance

Material: ADC12/Alu

Led light source: 3535/5050 PCB model: 14C8B,2C56B Weight of sink heat(kg): 5



| Model type | IP Rank | Beam angle | Heat sink dimensions |
|------------|---------|------------|-------------------------|
| FSD-JR | IP66 | 15/30° | 491*382*143n |









Super heat dissipation performance

Led light source: 3535/5050 PCB model: 13B6C,14B7C Weight of sink heat(kg): 1.4

Aluminium substrate specifications(mm): 76*150*1.6





| Model type | IP Rank | Power | Heat sink dimensions |
|------------|---------|---------|-------------------------|
| FSD-JR | IP66 | 60-120w | 336*216*182mr |







" Camping Light "



FSD-YH

Charging portable small power generation system

IP Rank: IP45

Warranty: 1 years

Voltage(v): 7.4

Rated power rating(w): 12

Overall dimensions(mm): 11.2 x 18 x 7.9





| Model type | Life span | Type of switch | Continuous lighting tim |
|------------|-----------|----------------|----------------------------|
| FSD-YH | 5000h | Induction type | 6-12 h |





FSD-YY

Strong adhesion, waterproof and dust-proof

IP Rank: IP45

Warranty: 1 years

Voltage(v): 6

Rated power rating(w): 5

Overall dimensions(mm):φ75*160





| Model type | Life span | Type of switch | Continuous lighting time |
|------------|-----------|----------------|-----------------------------|
| FSD-YY | 10000h | Induction type | 12-16 hour |







VNS-1905

Remote control button, intelligent light control

Working voltage(v): 3.7 Working current: 1.2A

Lithium battery capacity: 3.7V2200mAx 2pcs

Solar panel: 6V5W(monocrystalline silicon solar panel)





| Model type | LED | Charging time | Output powe |
|------------|--------|---------------|-------------|
| VNS-1905 | 136pcs | 8 hours | 7W |



" Holiday
Light "





LH


Solar power, intelligent light control

Working voltage(v): 6 Solar Panel: 600mA Size(cm): 27.2*13.2*7 Working current: 6mA





| Model type | NW | Material | IP Rating |
|------------|---------|------------|-----------|
| LH | 0.306kg | PC+LED+PVC | IP44 |





FSD-LH

LED rechargeable smoke lamp

Power Supplier: DC 5V USB

Leds Qty: 120L*4,(Can be customized)

Fucntion: 8fucntions Remote: 13 Keys Warranty: 5years





| Model type | Length | IP Rating | Flux lumineu |
|------------|---------|-----------|--------------|
| FSD-LH | 2*0.15m | IP44 | 75lm |



FSD-HY

Petal-shaped flame effect

Material: ABS

Solar Panel: Polysilicon solar panels

Light Source: LED

Working Temperature(°C): -20 - 60

Working Time: 6-12H





| Model type | G.W | Product size | Function |
|------------|-------|--------------|------------------------------|
| FSD-HY | 0.2kg | 98*95*246mm | Intelligent light control |



FSD-YQ

New shape of round torch

Material: ABS

Solar Panel: Monocrystalline silicon plate

Light Source: LED


Working Temperature(°C): -20 - 60





| Model type | G.W | Product size | Function |
|------------|--------|--------------|------------------------------|
| FSD-YQ | 0.48kg | 160*125mm | Intelligent light control |





" Plant Light "



FLG-650

Better canopy light penetration with diffused light

Dimming: 0-100%

PPFDµmol/(m2/s): 1287

Footprint: 4'x4'/5'x5'ft/6*6'FT

LED Light Source: Epistar 3030+660nm


Led driver: 1pc Inventronics driver Meanwell with knob dimmer





| Model type | Efficacy | Lamp Luminous Flux | Colour temperature |
|------------|----------|-----------------------|-----------------------|
| FLG-650 | 1500 | 220lm | 3000K+4000K |






















Process of production...

Inspection of incoming materials

 \approx

Production and assembly

×

Aging test

×

Integrating sphere test

×

IES Light distribution test

×

High and low pressure test

Water proof test

×

Product packaging

Shipment



« Die casting workshop Die casting workshop













« Machine working shop Machine working shop













« Powder spraying workshop Powder spraying workshop











Controller



« Assembly shop Assembly shop









Product Certification Certificate...

 Our products have passed CCC, FCC, UL, SAA, CE, RoHS, and many other intermational quality system certifications. • At present, our products have been exported to more than 70 countries in North America, South America, Europe, the Middle East, Africa, Southeast Asia, etc., and have been unanimously recognized by customers.















Case scenarios of different categories...

German Hardware Processing Factory (UFOH Mining Lamp)

Los Angeles Industrial Park (WK Wall Lamp)

Suzhou Pharmaceutical Cold Storage (UFOH mining lamp)

Spanish Football Stadium (FLH pitch lights)

Lithuania Airport (FLG Stadium lights)

Dongguan Shatin Logistics Park (UFOH Mining Lamps)

Swedish racecourse (UFOH mining lamp with lampshade)

German Football Stadium (FLL pitch lights)

Thai Road (SLB street light)

Xi 'an Workshop (UFOH Mining lamp)

Xi 'an Campus Stadium (FLP Floodlight)

Dominican Gas Station (CP gas station light)




















































ZHENGZHOU FIVE STAR LIGHTING CO., LTD.

www.fsdlighting.com

http://fivestarlight.en.alibaba.com

Tel: +86-371-63223999 Mob: +86-13598018017 E-mail: admin@fsdlighting.com NO.66 JINGSAN ROAD, JINSHUI DISTRICT, ZHENGZHOU, CHINA